



Size	600 x 600 x 50 mm
Weight	17 kg
Thread of tapped holes	M6

## 77 Series — 1/8 in. Skins (3 mm)

<b>Core:</b>	Steel honeycomb, closed-cell, 0.010 in. (0.2 mm) thick foil	
<b>Core shear modulus:</b>	275,000 psi (19,300 kg/cm <sup>2</sup> )	
<b>Core cell size:</b>	<0.5 in. <sup>2</sup> (3 cm <sup>2</sup> )	
<b>Core density:</b>	13.3 lb/ft <sup>3</sup> (230 kg/m <sup>3</sup> )	
<b>Flatness:</b>	± 0.005 in. (0.13 mm)	
<b>Top skin:</b>	430 series ferromagnetic stainless steel 1/8 in. (3 mm) thick	
<b>Sidewalls:</b>	Damped, formed steel channel, vinyl covered	
<b>Tapped holes:</b>	Backed by 1 in. (25 mm) long CleanTop® nylon cups	
<b>Weight Factor (WF) approximately; Area x WF = Total Weight:</b>		
	<b>2 in. Thick (50 mm)</b>	<b>4 in. Thick 100 mm)</b>
	0.100 lb/in. <sup>2</sup> 0.007 kg/cm <sup>2</sup>	0.150 lb/in. <sup>2</sup> 0.011 kg/cm <sup>2</sup>

Specifications provided by the manufacturer